



TRAVEL:

X-axis: 3000 mm (118.1")

Y-axis: 1700 mm (66.9")

Z-axis: 900 mm (35.4")

Description	UNIT	DMC-3018	
TRAVEL			
X-axis	MM(inch)	3000 (118)	
Y-axis	MM(inch)	1700 (67)	
Z-axis	MM(inch)	900 (35.4)	
Z-axis(O.P.)	MM(inch)	-	
Spindle nose to table surface	MM(inch)	120~1020	(4.7~40.1)
Distance between columns	MM(inch)	1800 (70.8)	
TABLE			
Dimension	MM(inch)	3200*1700	
(125.9 * 67)			
Working Area	MM(inch)	3000*1660	
(118 * 61.4)			
Tee Slots (W x No. x CD)	MM	22 x 9 x 200	
Max. Table Load	KG(lbs)	6,200/13,640	
Spindle			
Spindle speed(Built-in type)	rpm	18,000/20,000(O.P.)	
Spindle motor(Built-in type)			
Torque Max.	kw / NM	21kw / 200NM	
Spindle Taper	HSK 63A		
Spindle speed(Direct drive)	rpm	BT40: 12,000/15,000	
BT50: 8,000/10,000/12,000(O.P.)			
Dual-speed spindle motor			
Kw-Nm(L/H) (Direct drive) Controller			
Kw/Nm Faunc-			
- αT8 7.5kw-15,000rpm L:47Nm H:23.9Nm			
- αT15 18.5kw-12,000rpm L:102Nm H:28.6Nm			
- αL15 18.5kw-15,000rpm L:150Nm H:35Nm			
- αL26(18.5-22kw)10,000rpm L:286Nm H:88Nm			
- αB160LL(30kw)10,000rpm L:350Nm H:95Nm			
- αL8 (11-15kw)20,000rpm L:79.5Nm H:23.9Nm			
Mitsubishi-			
- SJ-VKRS30-06ZM			
22kw-10,000rpm			
L:286Nm H:88Nm			

Siemens-

- 1PM6138-2LF8
 22kw-10,000rpm
 L:140Nm H:53Nm

α22+ZF Gear Box α30+ZF (Direct drive)	(Direct Drive) H:8,000rpm L:1,500rpm/560NM(Max)
(After mounting gear box, the torque increase 4 times at low speed)	
H:8,000rpm/L:700rpm/1100NM	
SJ-V26+ZF Gear box(Direct drive)	(Direct Drive) H:8,000rpm L:1,500rpm/560NM(Max)
(After mounting gear box, the torque increase 4 times at low speed)	
H:8,000rpm/L:700rpm/1100NM	
Spindle Taper(o.p.)	BT40/DIN69871
BT50/DIN69871(O.P.)	
Feedrate	
Cutting feed	mm 1-10,000
Depending on controller	
X/Y axis rapid traverse(o.p.)mm	20,000
Z axis rapid traverse(o.p.)mm	12,000
X axis servo motor	
Y/Z axis servo motor	NM 30
22/30 (Z axis Hydraulic Balance)	
Linear guide (Roller type)	
X/Y/Z axis	mm X: 55*2pcs
Y: 45*2pcs + 25*1pcs	
Z: 55*2pcs	
Ballscrew	
X axis ballscrew dia x pitchmm	55 * 12
Y axis ballscrew dia x pitchmm	50 * 12
Z axis ballscrew dia x pitch45 * 10	
A.T.C	
Type of tool(HSK63A/BT40)	
Tool capacity	Armless
12(OP) 16/20	Armless type
Type of tool(BT40/BT50)	
Tool capacity	Arm
24/30 (Disc type)	Arm
32/40/60/80/120(Chain type)	
Max. tool diameter	MM(inch) BT50: 120(5")
Max. tool length	MM(inch) 300 (11.8")
Max. tool weight	kgs(lbs) BT50: 14(31")
Tool to tool time	sec. Armless Type:7
Air supply	kg/c ³ 6
Power supply	KVA 35
Coolant pump	HP 1HP * 2pcs
Machine weight	kgs(lbs) 28,500/62,700

- Raiser block 200mm(o.p.)mm -
- Raiser block 500mm(o.p.)mm -

Controller

